



Corecloud WLVS7103 Series High-Precision Data- Logging Wireless Low-Frequency Vibration and Tilt Monitor — Specification

2026-05-24

Rev.A

Copyright © 2019-now Corecloud Innovation Technology Co., Ltd. All Rights Reserved.

No part of this document may be excerpted, reproduced or distributed in any form without prior written permission of the Company.

Notice

The products, services or features you purchase are subject to Corecloud commercial contracts and terms. Some or all of the products, services or features described in this document may not be within the scope of your purchase or use. Unless otherwise agreed in the contract, Corecloud makes no express or implied statements or warranties regarding the contents of this document. The contents of this document are updated

Revision History

Version	Date	Description	Status
Rev.A	2026-05-24	Initial release	In Preview

Table of Contents

1 Product Overview 1

2 Key Features..... 2

 2.1 Synchronized Triple Measurement..... 2

 2.2 On-Sensor Edge Computing 2

 2.3 Large-Capacity Storage and Store-and-Forward 2

 2.4 Ultra-Low Power Consumption and Field Power Supply 3

 2.5 Industrial-grade environmental adaptability 3

 2.6 Plug-and-Play System Integration 4

3 Applications 5

4 Specifications 7

5 Interface and LED..... 11

6 Mechanical Dimensions..... 13

7 Accessories and Mounting 14

8 Installation Notes..... 14

9 Precautions..... 14

10 Ordering Information..... 15

List of Figures

Figure 1-1Product Photo 1

Figure 5-1Interface and LED Position 11

Figure 6-1Mechanical Dimensions (unit: mm)..... 13

List of Tables

Table 4-1 Specifications 7

Table 5-1 Interface and LED Definition..... 11

Table 7-1 Accessories and Mounting 14

Table 10-1 Ordering Information Overview..... 15

1 Product Overview



Figure 1-1 Product Photo

The Corecloud WLVS7103 series high-precision data-logging wireless low-frequency vibration and tilt monitor integrates triaxial vibration, triaxial tilt and temperature measurement in a wireless low-frequency monitoring instrument, designed for structural health monitoring (SHM). One device replaces three separate sensors - a vibration sensor, a tilt sensor and a thermometer - greatly simplifying on-site installation and data integration, and is especially suitable for field structural monitoring scenarios with dense measurement points and difficult power supply and wiring.

The core uses a MEMS accelerometer and a 24-bit $\Sigma\Delta$ ADC to achieve a 0 Hz DC frequency response, with noise density as low as 22 $\mu\text{g}/\sqrt{\text{Hz}}$ and triaxial synchronous acquisition at up to 4000 Hz. The built-in tilt engine has an accuracy of $\pm 0.01^\circ$ and temperature drift of $0.002^\circ/\text{C}$; measuring range $-50^\circ\text{C} \sim +150^\circ\text{C}$, typical accuracy $\pm 0.5^\circ\text{C}$. Supports three real-time data acquisition modes - acceleration / velocity / displacement; the sensor computes acceleration/velocity/displacement feature values and up to 16384-point FFT spectrum analysis, with built-in 8 GB large-capacity local storage supporting event triggering and store-and-forward.

Communication uses 4G Cat.1 all-network + MQTT 3.1.1 protocol for direct connection to mainstream IoT platforms. Built-in GNSS positioning supports GPS/BDS dual-mode satellite positioning, providing precise time synchronization and location tagging for monitoring data. Three-tier intelligent power management achieves up to 2 years of battery life, supporting vibration/timer dual wake-up. The IP68 fully sealed aluminum alloy housing with HBM 8 kV/15 kV ESD protection supports both bolt and steel cable tie mounting. The device has a 1.69-inch wide-temperature color OLED screen (160×128 resolution) for local viewing of device status and monitoring data.

2 Key Features

2.1 Synchronized Triple Measurement

Vibration, tilt and temperature are integrated into a single device, reducing the number of on-site sensors and wiring complexity.

- **Triaxial low-frequency vibration:**Max. $\pm 8g$ range, 0 Hz~1000Hz bandwidth, noise $22\mu g/\sqrt{Hz}$, capturing weak structural vibration from static to low and mid frequencies
- **Triaxial tilt:**Static accuracy $\pm 0.01^\circ$, temperature drift $0.002^\circ/C$, suitable for quasi-static structural deformation monitoring
- **Wide-range temperature measurement:**-50 $^\circ C$ ~+150 $^\circ C$, 0.0625 $^\circ C$ resolution, $\pm 0.5^\circ C$ accuracy, providing a temperature compensation reference for vibration and tilt

2.2 On-Sensor Edge Computing

All signal processing is completed on the sensor, which directly outputs engineering-ready physical quantities and reduces host computing power and bandwidth overhead.

- **Direct physical quantity output:**Acceleration (m/s^2), velocity (mm/s), displacement (μm), no post-processing required
- **Multi-dimensional feature values:**Acceleration/velocity peak and RMS, frequency peak, instantaneous temperature, pushed automatically
- **16384-point FFT:**Multi-scale spectrum analysis for precise identification of structural natural frequencies and modes
- **Dual-mode push:**Feature values and waveform data are independently configured with separate intervals, balancing trend monitoring and in-depth diagnosis
- **Three acquisition modes:**Real-time acceleration / velocity / displacement acquisition modes are configurable, directly outputting the corresponding physical quantity data

2.3 Large-Capacity Storage and Store-and-Forward

8 GB large-capacity local storage,, ensuring transient event capture and offline data integrity.

- **Event-triggered recording:**Automatically captures the complete waveform before and after a trigger when vibration exceeds the threshold
- **Store-and-forward:**Locally buffers data during communication interruption and automatically retransmits after recovery, with zero data loss
- **Precise timestamping:**Precise alignment of multi-node data supports correlation analysis
- **Large-capacity local storage:**8 GB storage space; triaxial single-precision floating point (4 bytes/point) continuous recording stores approx. one year at 20 Hz sampling and approx. 2 days at 4000 Hz, for long-term monitoring data preservation and on-demand retrieval and analysis

2.4 Ultra-Low Power Consumption and Field Power Supply

10500 lithium battery with three-tier power management achieves up to 2 years of autonomous operation, eliminating on-site power dependency.

- **Three-tier power consumption:**Standard mode ~500 h / Sleep mode ~1400 h / Power-off + wake-up mode ~2 years
- **Dual wake-up:**Vibration-triggered immediate acquisition start and timer-based periodic health reporting
- **Multipower options:**9~30 VDC wide voltage + USB 5 V + External battery VBAT 3.6~4.2 VDC, compatible with solar panels and other power supply schemes
- **Real-time battery status reporting:**MQTT pushes battery level and voltage, supporting proactive maintenance

2.5 Industrial-grade environmental adaptability

Fully sealed aluminum alloy structure, IP68 protection, wide operating temperature range, suitable for long-term harsh outdoor deployment.

- **IP68:**Fully sealed against dust and continuous immersion; the waterproof aviation connector retains its seal through repeated mating cycles
- **Aluminum alloy housing:**Excellent heat dissipation, corrosion resistance and UV resistance, with a designed service life exceeding 10 years
- **Wide temperature -20 °C~60 °C:**Extended-temperature component screening for all-climate use
- **Flexible mounting:**Φ7 bolt holes + steel cable tie slots, suitable for concrete, steel structures, pipes, etc.
- **Power interface:**Input undervoltage, overvoltage, overcurrent and reverse-polarity protection
- **communication interface:**30 kV ESD protection for both air discharge and contact discharge, with input overvoltage protection

2.6 Plug-and-Play System Integration

Zero-threshold USB flash-drive configuration and standard MQTT protocol for seamless integration with mainstream cloud platforms.

- **MQTT 3.1.1:** Direct connection to AWS IoT, Alibaba Cloud IoT, EMQX, etc., no custom development required
- **USB flash-drive configuration:** Plug-and-play recognition; edit a text file to set parameters, no driver or dedicated software required
- **4G Cat.1 global version:** GL global version
- **RS485 alarm interlocking:** Outputs a configurable alarm signal through the RS485 interface to interlock with external devices (cameras, sound-light alarms, PLCs, etc.), closing the monitoring-alarm-response loop
- **GNSS positioning:** Built-in GPS / BDS dual-mode positioning engine provides location tagging and time synchronization for monitoring data
- **Local OLED display:** 1.69-inch wide-temperature color screen, 160×128 resolution, for local viewing of device status, real-time data and alarm information
- **OTA upgrade:** MQTT remote firmware update, no on-site operation required

3 Applications

- **Geological hazard monitoring and early warning**

Landslides and collapses are progressive hazards that manifest as slight tilt changes and low-frequency microseisms before failure. Monitoring points are typically located in remote mountainous areas without mains power or wired networks. The WLVS7103 $\pm 0.01^\circ$ tilt accuracy detects millimeter-level slope displacement, and the 0 Hz vibration response captures microseism precursors; 2-year battery life eliminates the power dependency, 4G direct cloud connection requires no gateway; the IP68 aluminum alloy housing withstands extreme mountain weather and strong UV radiation.

Typical monitoring targets: expressway/railway slopes · open-pit mine waste dumps · tailings dams · reservoir banks · debris flow source areas · deep foundation pit support structures

- **Civil engineering structural health monitoring**

Bridges, tunnels, high-rise buildings and dams require simultaneous monitoring of dynamic response (vibration) and quasi-static deformation (tilt/settlement). The WLVS7103 provides vibration + tilt dual-dimension data from a single device with temporal correlation, supporting modal analysis and damage identification. 16384-point FFT precisely identifies structural natural frequencies. Large-capacity local storage ensures monitoring continuity during network interruption.

Typical monitoring targets: bridge piers and bearings · tunnel linings · high-rise building wind-induced vibration · dam crest displacement · stadium trusses · historic buildings

- **Power transmission and distribution infrastructure monitoring**

Transmission towers face multiple threats - wind vibration, conductor galloping, icing and foundation settlement - and are located in remote areas without power or networks. The WLVS7103's triaxial vibration captures wind-induced tower response, triaxial tilt detects foundation differential settlement, and temperature monitoring provides thermal expansion correlation data for conductor sag. Two-year battery life eliminates solar panels, and 4G direct connection avoids fiber deployment.

Typical monitoring targets: HV/UHV transmission towers · distribution poles in unstable geological areas · substation gantries · wind farm collector line towers

- **Rail transit infrastructure monitoring**

Track foundation degradation, bearing wear and lining deformation develop progressively over millions of load cycles and must be detected early. The WLVS7103's maximum 4000 Hz sampling covers the key frequency bands of train-induced vibration; event triggering automatically records waveforms at each train passage without continuous streaming. Tilt monitoring tracks long-term track settlement and pier deflection. Battery power avoids cabling operating lines.

Typical monitoring targets: metro tunnel segments · elevated bridge piers and bearings · track subgrade transition zones · railway turnouts · vibration impact assessment of adjacent construction

- **New energy facility structure monitoring**

Wind turbine towers bear complex loads from wind thrust and wave action; tower tilt indicates foundation integrity, and <1 Hz low-frequency vibration corresponds to the tower's natural frequency, a key parameter

for resonance avoidance. The WLVS7103's 0 Hz response captures sub-Hz tower oscillation, $\pm 0.01^\circ$ tilt detection of verticality changes caused by foundation settlement, and temperature monitoring distinguishes thermal expansion from structural deformation. MQTT integrates directly into SCADA systems.

Typical monitoring targets: onshore/offshore wind turbine towers · photovoltaic tracker bracket foundations · solar thermal heliostat foundations

- **Hydraulic and marine engineering structure monitoring**

Hydraulic structures such as sluices, pumping stations, embankments and offshore platforms experience low-frequency vibration and tilt caused by flow pulsation, wave impact and water level changes. The WLVS7103 IP68 protection withstands continuous immersion, 0 Hz frequency response captures flow-induced structural vibration, $\pm 0.01^\circ$ tilt detection of differential settlement and tilting trends. Battery power eliminates the safety risks and construction difficulty of wiring near water.

Typical monitoring targets: sluice piers · pumping station housings · embankments/flood walls · offshore platform jackets · cross-sea bridge foundations

4 Specifications

Unless otherwise specified, all parameters are tested at room temperature (25 °C).

Table 4-1 Specifications

Basic Parameters	Operating temperature range		-20°C~60°C
	Storage temperature range		-20 °C~45 °C (short-term storage) ⁽¹⁾ 15 °C~35 °C (long-term storage)
	IP protection rating		IP68
	Dimensions		156 × 79 × 58.8 mm
	Weight		approx. 720g
	Housing material		Aluminum alloy
	ESD rating		HBM 8 kV contact discharge, 15 kV air discharge
	Applicable standards		GB/T 17799.2 / 4208 / 2423.1 / 2423.2
System power supply	Internal power supply		3.7V 10500 mAh ternary lithium battery
	External power supply	DC / USB / VBAT	9~30VDC / 5VDC / 3.6~4.2VDC
	Charging power/time		5 W / typ. 8 h@5V1A
	Rated power	Off / Sleep / Running	50 μW / 30 mW / 85 mW (typ.)
	Operating time	Standard / Sleep / Power-off + Wake-up	approx. 500 h / approx.1400 h / approx. 2 years
Communication interface	Communication standard		4G Cat.1 all-network
	Communication speed		Typ. 50 KB/s ⁽²⁾
	Communication protocol		MQTT 3.1.1
	Satellite systems		GPS L1 / BDS B1I
	Sensitivity	Acquisition / Re-acquisition / Tracking	-143 / -155 / -157 dBm
	Positioning accuracy	CEP-50 (open areas)	≤1.6m

	RS485 alarm output	Configurable alarm signal	Interlocking with cameras, sound-light alarms, PLCs and other external devices
Configuration	Configuration interface		Waterproof USB aviation connector
	Configuration protocol		USB flash-drive file configuration
	Firmware update		Local USB flash-drive firmware upgrade / online OTA
System resources	Memory		512KB+8MB
	CPU		240 MHz, 800 CoreMark®
	Storage		8 GB local storage
	Display		1.69-inch color OLED, 160 × 128 resolution, wide-temperature operation
Sensor Performance	Sensor type		MEMS accelerometer (Analog output)
	A/D conversion		24-bit Σ - Δ ADC
	Axes		X / Y / Z triaxial
	Range		± 2 / ± 8 g
	Resolution		0.24 μ g (± 2 g range) / 0.95 μ g (± 8 g range) ⁽³⁾
	3 dB frequency response		0Hz~1000Hz ⁽⁴⁾
	Noise density		Typ. 22 μ g/ $\sqrt{\text{Hz}}$
	0-g / 1-g accuracy		± 0.2 mg (± 2 g range)
	Non-linearity		0.1% FS
	Temperature drift		0.03mg/°C
Signal processing	Sampling rate		4000 / 2000 / 1000 / 500 / 250 / 100 / 50 / 20 Hz
	FFT points		128 / 256 / 1024 / 2048 / 4096 / 8192 / 16384 points
	Feature output	value	Acceleration/velocity peak and RMS, frequency peak, instantaneous temperature
	Waveform output		Acceleration/velocity time-domain and frequency-domain waveforms
	Velocity range		0~500mm/s
	Velocity resolution		0.01mm/s
	Velocity accuracy	peak	± 0.5 mm/s (guaranteed above 10 Hz) ± 1 mm/s (guaranteed above 5 Hz) ± 5 mm/s (guaranteed above 1 Hz)
	Velocity accuracy	RMS	± 0.05 mm/s (0.1Hz guaranteed above)
	Displacement		0~50 mm

	range	
	Displacement	0.01mm
	resolution	
	Displacement	±0.1 mm (guaranteed above 5 Hz)
	peak accuracy	±0.5 mm (guaranteed above 2 Hz)
	Displacement	±0.05 mm (guaranteed above 2 Hz)
	peak-to-peak	±0.1 mm (guaranteed above 1 Hz)
	accuracy	±0.5 mm (guaranteed above 0.5 Hz)
Tilt measurement	Axes	X / Y / Z triaxial
	Range	±90°
	Resolution	0.001°
	Static accuracy	±0.01° ⁽⁵⁾
	Temperature drift	0.002°/°C ⁽⁶⁾
Temperature measurement	Range	-50°C~+150°C
	Resolution	0.0625°C
	Accuracy	-20°C~85 °C: typ. ±0.5°C -50°C~150 °C: typ. ±0.75°C
	Thermal response time	≤100s ⁽⁷⁾

⚠ Precautions

- (1) Short-term storage is less than 1 month.
- (2) MQTT protocol, QoS2 service level, sending 1 MB of data, average of 100 runs.
- (3) The acceleration signal is quantized by a 24-bit Σ - Δ ADC: ±2 g range 1 LSB $\approx$ 0.24 μ g (4 g/2²⁴), ±8 g range 1 LSB $\approx$ 0.95 μ g (16 g/2²⁴). When resolution is noise-limited, actual measurements prevail.
- (4) The upper 3 dB frequency response is limited by the configured sampling rate and is always below 0.5× the sampling rate.
- (5) Aging and other factors within the operating range are considered at constant temperature.
- (6) Maximum drift over the -20 °C~60 °C temperature range.
- (7) Time required at 25 °C room temperature for the sensor, placed in 85 °C silicone oil, to reach 63% of the final stable value.

⚠ Storage duration notes

Typical duration of continuous recording on the 8 GB storage, estimated for triaxial single-precision floating point (4 bytes/point) (conservative estimate, excluding file system overhead): approx. 2 days at 4000 Hz / 4 days at 2000 Hz / 8 days at 1000 Hz / 16 days at 500 Hz / 30 days at 250 Hz / 80 days at 100 Hz / 160 days at 50 Hz / 400 days at 20 Hz. Actual duration depends on storage content and push configuration.

⚠ Velocity and displacement accuracy notes

Velocity peak accuracy tiers: ±0.5 mm/s (guaranteed above 10 Hz, meeting the ISEE blast vibration monitor specification accuracy requirement of 2~250 Hz, i.e. the greater of ±5% or ±0.5 mm/s), ±1 mm/s (guaranteed above 5 Hz), ±5 mm/s (guaranteed above 1 Hz); velocity RMS accuracy ±0.05 mm/s (guaranteed above 0.1 Hz). Displacement peak accuracy: ±0.1 mm (guaranteed above 5 Hz), ±0.5 mm (guaranteed above 2 Hz); displacement

peak-to-peak accuracy: ± 0.05 mm (guaranteed above 2 Hz), ± 0.1 mm (guaranteed above 1 Hz), ± 0.5 mm (guaranteed above 0.5 Hz). Below the stated frequencies, MEMS non-linearity errors are amplified by $1/f$ and $1/f^2$ integration, exceeding the guaranteed accuracy range; outputs may deviate from the true value and should be used for trending only, not for precise quantitative measurement.

5 Interface and LED



Figure 5-1Interface and LED Position

The device is equipped with a 1.69-inch color OLED screen, 6 keys, 4 LEDs, two antenna interfaces (4G / GNSS) and two waterproof aviation connectors (USB / RS485). The LEDs fromtop tobottom, in order: LED RUN (system operating status), LED POWER (power status), LED TX (data transmission) and LED RX (data reception); the color OLED screen displays device information, configuration parameters and real-time data.

Table 5-1 Interface and LED Definition

Interface name	Definition
Power/confirm key	Press and hold to power off / press briefly to

			power on or wake the device
Navigation keys	Up / Down / Left / Right		Menu navigation and parameter selection; follow the on-screen prompts
Back key			Return to the previous menu; follow the on-screen prompts
USB connector	aviation	DP / DN	USB signals
		VBUS / GND	5 VDC power supply
RS485 connector	aviation	A / B or VBAT / GND	RS485 signals or External battery supply, 3.6~4.2 VDC input (VBAT multiplexed with RS485, defaults to 485; switchable by opening the housing)
		VDC / GND	9~30 VDC power supply
Status LED			Green blinking (normal)/ Red blinking (server not connected)
LED RUN			System operating status LED: Normal operation: green on for 100 ms, off for 1000 ms; Operating fault: red on for 100 ms, off for 100 ms
LED POWER			Power status: Red solid while charging / green solid when fully charged / red blinking below 20% battery
LED TX			LED indicating data transmission to the server: Data transmission: green on for 100 ms
LED RX			LED indicating data reception from the server: Data reception: green on for 100 ms
4G antenna			SMA female connector
GNSS ANT			GNSS antenna interface with an independent external antenna for receiving positioning signals

6 Mechanical Dimensions

Outline dimensions: 156 × 79 × 58.8 mm. Bottom $\Phi 7 \times 4$ mounting holes (7 mm diameter, compatible with common M6 expansion anchors) and steel cable tie slots, supporting bolt fastening and binding on irregular surfaces.






Figure 6-1 Mechanical Dimensions (unit: mm)

7 Accessories and Mounting

Table 7-1 Accessories and Mounting

Name	Specification	Image	Description
Aviation connector	M5 4-pin female to terminal block Wire color code: yellow (9-30VDC), white (GND), red (RS485-A), black (RS485-B)		Standard, RS485 and power connection
Aviation connector	M5 4-pin female to USB		Standard, USB connection
L-shaped bracket	Material: 201 stainless steel Thickness: 4 mm Mounting holes: $\Phi 7 \times 4$		Optional, vertical mounting bracket

8 Installation Notes

- Clean the mounting surface; fill rough surfaces with thermal grease to ensure tight contact.
- Align the sensor X/Y axes with the principal directions of the structure, keep the tilt measurement surface parallel to the measured surface, and calibrate the zero point after installation.
- $\Phi 7$ mounting holes compatible with M6 expansion anchors; tightening torque 3~5 N·m.
- Keep the 4G antenna vertical and away from metal obstructions; use a high-gain antenna in weak-signal areas.
- Tighten the locking nut of the aviation connector; for long-term outdoor use, add waterproof tape at the cable root as secondary protection.

9 Precautions

- Impact during use is prohibited.
- Long-term storage above 105 °C environment, otherwise sensor accuracy will be seriously degraded.
- Do not insert sharp objects into the silicone parts, to prevent damage to the IP68 protection and product

reliability.

- Excessive torque during installation is prohibited to prevent thread damage.
- The device contains a lithium battery; do not throw it into fire or short-circuit the battery contacts, and recycle the battery according to local regulations when discarded.
- For long-term storage (over 3 months), charge the battery to 50%~60% and store it in a dry 15 °C~25 °C environment, recharging every 6 months.

10 Ordering Information

Model code: WLVS7103-[Bandwidth]-[Region]

Bandwidth: 1KT = 1000 Hz triaxial

Region: GL

Table 10-1 Ordering Information Overview

Name		Model	Specification
High-precision data-logging wireless low-frequency vibration and tilt monitor		WLVS7103-1KT-GL	1000 Hz bandwidth, global version 4G